

**595mm x 595mm Direct/Indirect Luminaire - 36W 3,800lm - Low Glare High Uniformity Commercial Office LED Luminaire**

**£35.00**



36W 3,800lm direct / in-direct LED 595 x 595mm luminaire for offices & commercial environments. High uniformity, low-glare diffuser ensures this LED panel assists with LG3 / LG7 compliance hence giving a UGR<19. Industry leading efficacy of 95lm/W, with added benefit of long-term maintenance & serviceability of luminaire possible. Further options of dimmable: DALI / 1-10V, as well as built-in microwave sensor (-MI) for occupancy detection, or built-in PIR sensor (-PIR) for occupancy detection and daylight dimming functionality. 3-hour emergency version also available with self-test and LED indicator light.

**PRODUCT INFORMATION**

LED Type	SMD2835 LEDs
Warranty	5 Year
Part L Compliant	Yes
Dimensions	595mm x 595mm x 96mm
Weight	4.6kg
Equivalent to	4 x 18W T8 Louvre

**TECHNICAL SPECIFICATIONS**

Power Consumption	36W
Input Voltage	110-280V AC
Power Factor	>0.95
Operating Temperature	-20°C to 50°C
L70 Rated Lifetime	+45,000hrs
Ingress Protection	IP21
Emergency Battery Type	YUASA® 12V 1300mAh NiCd

**LUMEN PERFORMANCE**

Luminous Efficiency	106lm/W
Beam Angle	120°
CRI (Colour Rendering Index)	>80Ra
Lumen Output	3,800lm

**AVAILABLE OPTIONS**

Colour Temperature	Pure White (5500-6000K)
3-Hour Emergency Version	Available Variant
1-10V Dimmable	Yes