

LED Wallpack - 40W 4,800lm - Die-cast aluminium Body with 5mm Glass - Replacement for 70W MHL Metal Halide Replacements Flicker Free

\$68.35














50,000+ Hours Lifespan




Built to last & Easy to install

INSTALLATION INSTRUCTIONS:



1. Loosen screws and slide up the front cover carefully from the bottom using
2. Remove 20mm rubber strips from covers (optional) to fit the waterproof gasket and double-paneled cover.
3. Drilling out the hole(s) to secure it on the wall with appropriate screws.
4. Fit and tighten up per wiring diagram.
5. Check the fitting and tighten the screws to lock.






40W IP65 LED wallpack is a favourite of councils, schools and local authority, with an 5mm glass reflector and die-cast aluminium body for durability. Powder coated [fade and abrasion resistant, electrostatically applied, thermally cured, triglycidal isocyanurate (TGIC) textured polyester powder-coating] black finish for a classic luminaire design, whilst being up to 60% more energy efficient and fit-and-forget with a +50,000 hour rated lifetime. High operational efficacy of 120lm/W. IP65 sealed die-cast aluminium housing, hinged for ease of maintenance and installation, unit suitable for general purpose wall mount area and security lighting in a range of out-building applications such as public sector, walkways etc.

[DOWNLOAD PRODUCT INSTALLATION MANUAL / GUIDE](#)

PRODUCT INFORMATION

LED Type	Epstar SMD2835 LEDs
Warranty	5 Year
Part L Compliant	Yes
Dimensions	365mm x 235mm x 190mm
Weight	3.95kg
Equivalent to	70W MHL Wallpack

TECHNICAL SPECIFICATIONS

Power Consumption	40W
Input Voltage	100-280V AC
Power Factor	>0.95
Operating Temperature	-20°C to 50°C
L70 Rated Lifetime	+50,000hrs
Ingress Protection	IP65

LUMEN PERFORMANCE

Luminous Efficiency	120lm/W
Beam Angle	140°
CRI (Colour Rendering Index)	>80Ra
Lumen Output	4,800lm

AVAILABLE OPTIONS

Colour Temperature	Cool White (6500-7000K)
3-Hour Emergency Version	No
Built-in Microwave Occupancy Detector	No
1-10V Dimmable	On Request
DALI Dimmable	On Request
DMX 512 Compatible	No