

LED Recessed Canopy Light for Petrol Station Forecourt - IP65 60W / 150W SON / 70W MHL

\$228.70

60W
Replaces
150W / 70W
SON / MHL



PRODUCT INFORMATION

| | |
|------------------|----------------------|
| LED Type | SMD3030 LEDs |
| Warranty | 5 Year |
| Part L Compliant | Yes |
| Dimensions | 350mm x 262mm x 72mm |
| Weight | 4.5kg |
| Socket Type | N/A |
| Equivalent to | 150 SON |

TECHNICAL SPECIFICATIONS

| | |
|-----------------------|---------------|
| Power Consumption | 60W |
| Input Voltage | 110-280V AC |
| Power Factor | >0.95 |
| Operating Temperature | -20°C to 50°C |
| L70 Rated Lifetime | +50,000hrs |
| Ingress Protection | IP65 |

LUMEN PERFORMANCE

| | |
|------------------------------|-----------|
| Luminous Efficiency | 110lm/W |
| Beam Angle | 90° x 90° |
| CRI (Colour Rendering Index) | >80Ra |
| Lumen Output | 6,000lm |

AVAILABLE OPTIONS

| | |
|---------------------------------------|----------------------|
| Colour Temperature | Pure White (5000K) |
| 3-Hour Emergency Version | No |
| Built-in Microwave Occupancy Detector | No |
| 1-10V Dimmable | Available on Request |
| DALI Dimmable | Available on Request |

LED Recessed canopy light designed specifically industrial and exterior recessed ceiling canopies such as fuel stations, industrial clean-room applications and others. Finished in a rugged RAL White powder coated aluminium housing with

tempered, stabilised, impact resistant PMMA lens, the recessed canopy luminaire is suitable for extreme climates & environments from -20°C to +50°C. www.experts.co.uk/

A range of lumen packages from 60W - 150W, up to 19,000lm hence suitable for mount heights up to 12m - making a suitable direct replacement for 400W SON fittings energy efficient low luminous decay and maintenance were key factors in the luminaire design, meaning annual re-lamp, expensive lift equipment and inconvenience is negligible, as well as a much sought after energy savings of 75%.

Durable with rated life span of +50,000 hours / No UV or IR emissions / Instant on & Flicker free / CE & RoHS international standards / Environmentally friendly & part recyclable: no mercury or other hazardous materials used / RAL White powder coated aluminium heat sink / PMMA optics / Meanwell™ HLG Driver.