

LED Bollard Car Park Amenity Pathway Footpath 10W IP65 - Die-Cast Aluminium

\$68.36

850lm

995mm x
Ø120mm
10W



IK10



PRODUCT INFORMATION

LED Type	CREE LEDs
Warranty	5 Year
Part L Compliant	Yes
Dimensions	995mm x Ø120mm
Weight	3.2kg

TECHNICAL SPECIFICATIONS

Power Consumption	10W
Input Voltage	100 - 240V AC
Power Factor	>0.96
Operating Temperature	-20°C to 50°C
L70 Rated Lifetime	+100,000hrs
Ingress Protection	IP65

LUMEN PERFORMANCE

Luminous Efficiency	85lm/W
Beam Angle	120° x 120°
CRI (Colour Rendering Index)	>70Ra
Lumen Output	850lm

AVAILABLE OPTIONS

Colour Temperature	Natural White 4000-4500K
--------------------	--------------------------

The LED Bollard is a complete luminaire supplied with optional ground fixing kit (this can be selected in the dropdown menu)

and suitable for outdoor use being IP65 rated. Typical applications include car parks, walkways, parks and gardens, security areas, amenity areas and prestigious grounds. The unit features an internal frosted diffuser coupled with a silver optical controller to ensure minimal upward glare and a symmetrical spread of light. The LED Bollard is manufactured from die-cast aluminium and features a strong transparent UV stabilised polycarbonate diffuser which provides high efficiency and vandal resistance. The unit benefits from an IK10 mechanical impact rating and minimised maintenance being rated at 100,000+ lifetime hours. Other benefits include high light output, even in cold temperatures and minimised disturbance to wildlife due to non ultra violet light.

[Bollard Installation Detail](#)

[View Laboratory Test Data Certificate](#)