

## LED Premium Street Light 40w - 3-6M Column Street Lighting Fixture Flicker Free - Dark Sky Friendly 3000K/4000K 0% ULOR


**\$111.74**

**5,600lm**

**40W**  
Replaces  
**70W SON**



### LED Premium Street Light DIMENSIONS



### Performance-Optimized Design & Robust Construction



### PHOTOCELL ENABLED

FOR UP TO 80% SAVINGS ON ELECTRICITY



### DURABLE, ROBUST AND DEPENDABLE

ULOR 0% Flicker, 0% Humming



**24/7 CUSTOMER SUPPORT**

**LED Premium Street Light**

5m and elegant aesthetics  
Superior efficacy up to 140 lm/W  
Wide range of lumen packages  
Self-cleaning Smooth Surface  
Tool-less Access

**Free Lighting Design Service**

Unsure of how many lights you require?  
Concern about layout, life-time and lumens?  
Don't worry, our expert lighting designers are here to help.  
Enquire about our **FREE** no obligation lighting design service.  
Turned around & within just 48 hours!

**INSTALLATION INSTRUCTIONS:**

1. Remove the light head from the mounting bracket.
2. Insert the mounting bracket into the hole in the mounting plate.
3. Tighten the screw to secure the mounting bracket.
4. Insert the light head into the mounting bracket.
5. Tighten the screw to secure the light head.
6. The light head is now securely mounted to the mounting plate.

**INSTALLATION INSTRUCTIONS:**

1. Optional: Connect the light head to the photocell sensor.
2. Connect the light head to the photocell sensor.
3. Connect the light head to the photocell sensor.
4. Connect the light head to the photocell sensor.
5. Connect the light head to the photocell sensor.
6. Connect the light head to the photocell sensor.

### DARK SKY FRIENDLY



**3000K\***



### PRODUCT INFORMATION

LED Type	SMD3030 LEDs
Warranty	5 Year
Part L Compliant	Yes
Dimensions	617mm x 212mm x 118mm
Weight	3.85kg
Windage	0.08m <sup>2</sup>
Socket Type	Optional 3 pin NEMA Socket
Equivalent to	70 SON

### TECHNICAL SPECIFICATIONS

Power Consumption	40W
Input Voltage	100-280V AC
Power Factor	>0.96
Operating Temperature	-20°C to 50°C
L70 Rated Lifetime	+100,000hrs

## PRODUCT INFORMATION

## TECHNICAL SPECIFICATIONS

Ingress Protection IP66

### LUMEN PERFORMANCE

Luminous Efficiency 140lm/W

Beam Angle 150° x 80°

CRI (Colour Rendering Index) >80Ra

Lumen Output 5,600lm

### AVAILABLE OPTIONS

Colour Temperature 3000K (Dark Sky Friendly- 0% ULOR) 4000K

3-Hour Emergency Version No

Built-in Microwave Occupancy Detector No

1-10V Dimmable Available on Request

DALI Dimmable Available on Request

Luminaire designed for column/post mounting at heights of 4 - 16m, with a range of sizes across 30W - 240W (4,200-33,000lm), IP66 design for exterior environments, with a low profile, sleek silver anodised aluminum body for harsh weather environments, Premium Street light is for urban applications such as car-parks, pathways and pedestrian areas. PMMA optic lens ensures a high degree of uniformity across a range of spaces and reduced light spillage, thus further enhancing this 140lm/W luminaire to give optimum lux levels through out. Furthermore the Premium Street light is compatible with standard mains photocells. Additional benefits include 100,000 hours maintenance free performance, with no-tools/quick release access to the internal control gear for installation. Unit available with either 60mm or 76mm entry bracket for both bottom & side-entry hence universally compatible. Angle of illumination can be adjusted around 10° for increased spread.

[DOWNLOAD PRODUCT INSTALLATION MANUAL / GUIDE](#)

[DOWNLOAD UKAS LABORATORY TEST DATA & COMPLIANCE CERTIFICATES](#)

[DOWNLOAD UKAS LABORATORY TEST DATA & COMPLIANCE CERTIFICATES](#)

[DOWNLOAD UKAS LABORATORY TEST DATA & COMPLIANCE CERTIFICATES](#)



Unit 2,  
Delta Court,  
Doncaster,  
DN9 3GN  
text\_phone 03333 444 943  
sales@theledstore.co | <https://ledexperts.co.uk/>