

**LED Premium Street Light 60w - 4-6m Column Street Lighting Fixture - Dark Sky Friendly 3000K/4000K 0% ULOR**


**\$128.64**

**8,400lm**


**60W**  
Replaces  
**100W SON**



**LED Premium Street Light DIMENSIONS**



**Performance-Optimized Design & Robust Construction**



**PHOTOCELL ENABLED**



**DURABLE, ROBUST AND DEPENDABLE**



**24/7 CUSTOMER SUPPORT**

**LED Premium Street Light**  
Slim and elegant aesthetic.  
Superior efficacy up to 140 lm/W  
Wide range of lumen packages  
Self-cleaning Smooth Surface  
Tool-less Access

**INSTALLATION INSTRUCTIONS:**

**INSTALLATION INSTRUCTIONS:**

**DARK SKY FRIENDLY**



**Free Lighting Design Service**

Unsure of how many lights you require?  
Concern about layout, fit, wiring and lumens?  
Don't worry, our expert lighting designers are here to help.  
Enquire about our **FREE no obligation** lighting design service.  
Turned around & within just 48 hours!



**PRODUCT INFORMATION**

LED Type	SMD3030 LEDs
Warranty	5 Year
Part L Compliant	Yes
Dimensions	617mm x 212mm x 118mm
Weight	5.35kg
Windage	0.13m <sup>2</sup>
Socket Type	Optional 3 pin NEMA Socket
Equivalent to	70 MHL

**TECHNICAL SPECIFICATIONS**

Power Consumption	60W
Input Voltage	100-280V AC
Power Factor	>0.96
Operating Temperature	-20°C to 65°C
L70 Rated Lifetime	+100,000hrs

**PRODUCT INFORMATION****TECHNICAL SPECIFICATIONS**

Ingress Protection IP66

**LUMEN PERFORMANCE**

Luminous Efficiency 140lm/W

Beam Angle 80° x 150°

CRI (Colour Rendering Index) >80Ra

Lumen Output 8,400lm

**AVAILABLE OPTIONS**

Colour Temperature 3000K (Dark Sky Friendly- 0% ULOR) 4000K

3-Hour Emergency Version No

Built-in Microwave Occupancy Detector No

1-10V Dimmable Available on Request

DALI Dimmable Available on Request

Luminaire designed for column/post mounting at heights of 4 - 16m, with a range of sizes across 30W - 240W (4,200-33,000lm). IP66 design for exterior environments, with a low profile, sleek silver anodised aluminum body for harsh weather environments, Premium Street light is for urban applications such as car-parks, pathways and pedestrian areas. PMMA optic lens ensures a high degree of uniformity across a range of spaces and reduced light spillage, thus further enhancing this 140lm/W luminaire to give optimum lux levels through out. Furthermore the Premium Street light is compatible with standard mains photocells. Additional benefits include 100,000 hours maintenance free performance, with no-tools/quick release access to the internal control gear for installation. Unit available with either 60mm or 76mm entry bracket for both bottom & side-entry hence universally compatible. Angle of illumination can be adjusted around 10° for increased spread.

[DOWNLOAD PRODUCT INSTALLATION MANUAL / GUIDE](#)

[DOWNLOAD UKAS LABORATORY TEST DATA & COMPLIANCE CERTIFICATES](#)

[DOWNLOAD UKAS LABORATORY TEST DATA & COMPLIANCE CERTIFICATES](#)

[DOWNLOAD UKAS LABORATORY TEST DATA & COMPLIANCE CERTIFICATES](#)



Unit 2,  
Delta Court,  
Doncaster,  
DN9 3GN  
text\_phone 03333 444 943  
sales@theledstore.co | <https://ledexperts.co.uk/>