



**£131.55**



Technical diagram of the 4000 Series fire extinguisher, highlighting the 40-60mm side entry and 76mm bottom entry. The diagram shows the internal structure with various components labeled:

- Tool-less/quick release access
- Built-in 10KV surge protection
- Automatic electrical isolation when opened
- Replaceable gas tray with 5 firearm dry agent
- Organophosphorus weatherproof gas for harsh environments (PM)
- High quality and advanced design of one-piece die-cast housing provides strong protection and durability ensuring heat dissipation
- Target for 40-60mm side entry and 76mm bottom entry

Diagram illustrating the Dusk-to-Dawn sensor and its shorting cap. The sensor is shown with a blue cap. A callout shows the shorting cap being placed over the sensor's contacts.



3000K\*



LED Type	SMD3030 LEDs
Warranty	5 Year
Part L Compliant	Yes
Dimensions	617mm x 212mm x 118mm
Weight	3.85kg
Windage	0.08m <sup>2</sup>
Socket Type	Optional 3 pin NEMA Socket
Equivalent to	70 SON

Power Consumption	50W
Input Voltage	100-280V AC
Power Factor	>0.96
Operating Temperature	-20°C to 50°C
L70 Rated Lifetime	+100,000hrs

## PRODUCT INFORMATION

## TECHNICAL SPECIFICATIONS

Ingress Protection IP66

### LUMEN PERFORMANCE

Luminous Efficiency 140lm/W  
Beam Angle 150° x 80°  
CRI (Colour Rendering Index) >80Ra  
Lumen Output 7,000lm

### AVAILABLE OPTIONS

Colour Temperature 3000K (Dark Sky Friendly- 0% ULOR) 4000K  
3-Hour Emergency Version No  
Built-in Microwave Occupancy Detector No  
1-10V Dimmable Available on Request  
DALI Dimmable Available on Request

**\*\*Fitting Comes inclusive with integral 3-Pin NEMA Socket and Lucy Zodion 70lux Photocell\*\***

Luminaire designed for column/post mounting at heights of 4 - 16m, with a range of sizes across 20W - 240W (2,800-33,000lm), IP66 design for exterior environments, with a low profile, sleek silver anodised aluminum body for harsh weather environments, Premium Street light is for urban applications such as car-parks, pathways and pedestrian areas. PMMA optic lens ensures a high degree of uniformity across a range of spaces and reduced light spillage, thus further enhancing this 140lm/W luminaire to give optimum lux levels through out. Furthermore the Premium Street light is compatible with standard mains photocells. Additional benefits include 100,000 hours maintenance free performance, with no-tools/quick release access to the internal control gear for installation. Unit available with either 60mm or 76mm entry bracket for both bottom & side-entry hence universally compatible. Angle of illumination can be adjusted around 10° for increased spread.

[DOWNLOAD PRODUCT INSTALLATION MANUAL / GUIDE](#)

[DOWNLOAD UKAS LABORATORY TEST DATA & COMPLIANCE CERTIFICATES](#)

[DOWNLOAD UKAS LABORATORY TEST DATA & COMPLIANCE CERTIFICATES](#)

[DOWNLOAD UKAS LABORATORY TEST DATA & COMPLIANCE CERTIFICATES](#)



Unit 2,  
Delta Court,  
Doncaster,  
DN9 3GN  
text\_phone 03333 444 943  
sales@theledstore.co | <https://ledexperts.co.uk/>