

LED Premium Street Light 20w - 3-6M Column Street Lighting Fixture - Dark Sky Friendly 3000K/4000K 0% ULOR


£73.06

2,800lm

20W
Replaces
35W SOX



LED Premium Street Light DIMENSIONS



Performance-Optimized Design & Robust Construction



PHOTOCELL ENABLED

FOR UP TO 80% SAVINGS ON ELECTRICITY



DURABLE, ROBUST AND DEPENDABLE

ULOR 0% (0% ULOR, 0% ULOR, 0% ULOR)



24/7 CUSTOMER SUPPORT

LED Premium Street Light

5m and elegant aesthetic
Superior efficacy up to 140 lm/W
Wide range of lumen packages
Self-cleaning smooth surface
Tool-less Access

Free Lighting Design Service

Unsure of how many lights you require?
Concern about layout, life-time and lumens?
Don't worry, our expert lighting designers are here to help.
Enquire about our **FREE** no obligation lighting design service.
Turned around & within just 48 hours!

INSTALLATION INSTRUCTIONS:

1. Remove the mounting bracket from the light fixture.
2. Attach the mounting bracket to the light fixture.
3. Attach the mounting bracket to the light fixture.
4. Attach the mounting bracket to the light fixture.
5. Attach the mounting bracket to the light fixture.
6. Attach the mounting bracket to the light fixture.

INSTALLATION INSTRUCTIONS:

1. Remove the mounting bracket from the light fixture.
2. Attach the mounting bracket to the light fixture.
3. Attach the mounting bracket to the light fixture.
4. Attach the mounting bracket to the light fixture.
5. Attach the mounting bracket to the light fixture.
6. Attach the mounting bracket to the light fixture.

DARK SKY FRIENDLY



3000K*



PRODUCT INFORMATION

LED Type	SMD3030 LEDs
Warranty	5 Year
Part L Compliant	Yes
Dimensions	617mm x 212mm x 118mm
Weight	3.85kg
Windage	0.08m ²
Socket Type	Optional 3 pin NEMA Socket
Equivalent to	70 SON

TECHNICAL SPECIFICATIONS

Power Consumption	20W
Input Voltage	100-280V AC
Power Factor	>0.96
Operating Temperature	-20°C to 50°C
L70 Rated Lifetime	+100,000hrs

PRODUCT INFORMATION

TECHNICAL SPECIFICATIONS

Ingress Protection IP66

LUMEN PERFORMANCE

Luminous Efficiency 140lm/W

Beam Angle 150° x 80°

CRI (Colour Rendering Index) >80Ra

Lumen Output 2,800lm

AVAILABLE OPTIONS

Colour Temperature 3000K (Dark Sky Friendly- 0% ULOR) 4000K

3-Hour Emergency Version No

Built-in Microwave Occupancy Detector No

1-10V Dimmable Available on Request

DALI Dimmable Available on Request

Luminaire designed for column/post mounting at heights of 4 - 16m, with a range of sizes across 30W - 240W (4,200-33,000lm), IP66 design for exterior environments, with a low profile, sleek silver anodised aluminium body for harsh weather environments, Premium Street light is for urban applications such as car-parks, pathways and pedestrian areas. PMMA optic lens ensures a high degree of uniformity across a range of spaces and reduced light spillage, thus further enhancing this 140lm/W luminaire to give optimum lux levels through out. Furthermore the Premium Street light is compatible with standard mains photocells. Additional benefits include 100,000 hours maintenance free performance, with no-tools/quick release access to the internal control gear for installation. Unit available with either 60mm or 76mm entry bracket for both bottom & side-entry hence universally compatible. Angle of illumination can be adjusted around 10° for increased spread.

[DOWNLOAD PRODUCT INSTALLATION MANUAL / GUIDE](#)

[DOWNLOAD UKAS LABORATORY TEST DATA & COMPLIANCE CERTIFICATES](#)

[DOWNLOAD UKAS LABORATORY TEST DATA & COMPLIANCE CERTIFICATES](#)

[DOWNLOAD UKAS LABORATORY TEST DATA & COMPLIANCE CERTIFICATES](#)



Unit 2,
Delta Court,
Doncaster,
DN9 3GN
text_phone 03333 444 943
sales@theledstore.co | <https://ledexperts.co.uk/>