

**LED Premium Street Light 20w - 3-6M Column Street Lighting Fixture - Dark Sky Friendly 3000K/4000K 0% ULOR**


**£73.06**

**2,800lm**

**20W**  
Replaces  
**35W SOX**



**LED Premium Street Light DIMENSIONS**



**Performance-Optimized Design & Robust Construction**



**PHOTOCELL ENABLED**

FOR UP TO 80% SAVINGS ON ELECTRICITY



**DURABLE, ROBUST AND DEPENDABLE**

CLASS 1, CLASS 2 AND CLASS 3



**24/7 CUSTOMER SUPPORT**

**LED Premium Street Light**  
Slim and elegant aesthetic  
Superior efficacy up to 140 lm/W  
Wide range of lumen packages  
Self-cleaning smooth surface  
Tool-less Access

**INSTALLATION INSTRUCTIONS:**

**INSTALLATION INSTRUCTIONS:**

**DARK SKY FRIENDLY**



**Free Lighting Design Service**

Unsure of how many lights you require?  
Confused about layout, fit, levels and lumens?  
Don't worry, our expert lighting designers are here to help.  
Enquire about our **FREE no obligation** lighting design service.  
Turned around & within just 48 hours!



**PRODUCT INFORMATION**

LED Type	SMD3030 LEDs
Warranty	5 Year
Part L Compliant	Yes
Dimensions	617mm x 212mm x 118mm
Weight	3.85kg
Windage	0.08m <sup>2</sup>
Socket Type	Optional 3 pin NEMA Socket
Equivalent to	70 SON

**TECHNICAL SPECIFICATIONS**

Power Consumption	20W
Input Voltage	100-280V AC
Power Factor	>0.96
Operating Temperature	-20°C to 50°C
L70 Rated Lifetime	+100,000hrs

**PRODUCT INFORMATION****TECHNICAL SPECIFICATIONS**

Ingress Protection IP66

**LUMEN PERFORMANCE**

Luminous Efficiency 140lm/W

Beam Angle 150° x 80°

CRI (Colour Rendering Index) >80Ra

Lumen Output 2,800lm

**AVAILABLE OPTIONS**

Colour Temperature 3000K (Dark Sky Friendly- 0% ULOR) 4000K

3-Hour Emergency Version No

Built-in Microwave Occupancy Detector No

1-10V Dimmable Available on Request

DALI Dimmable Available on Request

Luminaire designed for column/post mounting at heights of 4 - 16m, with a range of sizes across 30W - 240W (4,200-33,000lm), IP66 design for exterior environments, with a low profile, sleek silver anodised aluminium body for harsh weather environments, Premium Street light is for urban applications such as car-parks, pathways and pedestrian areas. PMMA optic lens ensures a high degree of uniformity across a range of spaces and reduced light spillage, thus further enhancing this 140lm/W luminaire to give optimum lux levels through out. Furthermore the Premium Street light is compatible with standard mains photocells. Additional benefits include 100,000 hours maintenance free performance, with no-tools/quick release access to the internal control gear for installation. Unit available with either 60mm or 76mm entry bracket for both bottom & side-entry hence universally compatible. Angle of illumination can be adjusted around 10° for increased spread.

[DOWNLOAD PRODUCT INSTALLATION MANUAL / GUIDE](#)

[DOWNLOAD UKAS LABORATORY TEST DATA & COMPLIANCE CERTIFICATES](#)

[DOWNLOAD UKAS LABORATORY TEST DATA & COMPLIANCE CERTIFICATES](#)

[DOWNLOAD UKAS LABORATORY TEST DATA & COMPLIANCE CERTIFICATES](#)



Unit 2,  
Delta Court,  
Doncaster,  
DN9 3GN  
text\_phone 03333 444 943  
sales@theledstore.co | <https://ledexperts.co.uk/>