

# LED ECO Street Lantern Light 40W/5,600lm c/w Photocell NEMA Dusk til Dawn Sensor

**\$109.19**

**5,600lm**



**40W**  
Replaces  
**70W SON**



**LED Eco Street Lantern Light DIMENSIONS** DURABLE, ROBUST AND DEPENDABLE

**PHOTOCELL ENABLED** FOR UP TO 80% SAVINGS ON ELECTRICITY

Performance-Optimized Design & Robust Construction

Shorting Cap  
Dusk-to-Dawn sensor

Easy installation  
Slide the Fixed Cable Tail  
Securely Locking  
Post into a 30mm  
with Optional Adjustable Bracket

Adjustable 180°  
to accommodate from  
10° to 120°

Applications:  
Roads, Industrial, Car parks

OPTIONAL:  
Dimming, Flicker-free, Ultra-bright

**24/7 CUSTOMER SUPPORT** **5 Year Warranty**

**Free Lighting Design Service**

Unsure of how many lights you require?  
Confused about layout, site needs and sensors?  
Don't worry, our expert lighting designers are here to help.  
Enquire about our **FREE** no obligation lighting design service.  
\*Valid around the UK only. Just 48 hours!

**LED Eco Street Lantern Light**  
Superior efficacy up to 140 lm/W  
Wide range of lumen packages  
Self-cleaning Smooth Surface  
Low total cost of ownership  
Optically enhanced for residential light

**PRODUCT INFORMATION**

LED Type	LM80 3030 LEDs
Warranty	5 Year
Part L Compliant	Yes
Dimensions	370mm x 225mm x 93mm
Weight	2.5kg
Windage	0.08m <sup>2</sup>
Socket Type	60mm Side Entry 76mm Post Top Entry (with Adjustable Bracket)
Equivalent to	3-6m 70W SON

**TECHNICAL SPECIFICATIONS**

Power Consumption	40W
Input Voltage	100-277V AC
Power Factor	>0.95
Operating Temperature	-40°C to 50°C
L70 Rated Lifetime	+50,000hrs
Ingress Protection	IP66

**LUMEN PERFORMANCE**

Luminous Efficiency	140lm/W
Beam Angle	150° x 80°
CRI (Colour Rendering Index)	>70Ra
Lumen Output	5,600lm

**AVAILABLE OPTIONS**

**PRODUCT INFORMATION****TECHNICAL SPECIFICATIONS****LUMEN PERFORMANCE****AVAILABLE OPTIONS**

Colour Temperature	Natural White (4000-4500K)
3-Hour Emergency Version	No
Built-in Microwave Occupancy Detector	No
1-10V Dimmable	Available on Request
DALI Dimmable	Available on Request

**\*\*Fitting Comes inclusive with integral 3-Pin NEMA Socket and Lucy Zodion 70lux Photocell\*\***

The LED ECO Street Lantern Light is an economical solution for a wide range of exterior lighting applications. The luminaire comes in a range of lumen packages from 20-60W and is designed for column/post mounting at heights of 3 - 8m. The IP66 body is designed for exterior environments, with a sleek silvery grey die-cast aluminium body for harsh weather environments and an IK09 mechanical impact rating.

The luminaire is great for urban applications such as car parks, roads, foot paths, residential areas, housing developments, zebra crossings and pedestrian areas. The PMMA optic lens ensures a high degree of uniformity across a range of spaces and reduced light spillage, thus further enhancing this 140lm/W efficacy of this light to give optimum lux levels throughout. Furthermore, the LED ECO Street Lantern Light features an inbuilt 3-pin NEMA socket and Lucy Zodion photocell dusk til dawn sensor for further energy savings.

Additional benefits of the light include a +50,000hour maintenance free performance and minimal disturbance to nocturnal wildlife due to the lack of the UV/IR spectrum associated with LED photometric characteristics.

The LED ECO Street Lantern Light is 60mm side entry unit as standard, but has the option of an additional adjustable tilt bracket which mounts direct onto a 76mm column (available as an extra in the drop down options). This bracket can be adjusted -10° to +20° from the horizontal plane.

[DOWNLOAD PRODUCT INSTALLATION MANUAL / GUIDE](#)