

**30W LED Top Hat Lantern c/w Photocell Dusk-til-dawn sensor - 360 Degree Car Park / Street Light Luminaire 30W c/w Photocell Dusk-til-dawn sensor**

**\$294.02**

**3,750lm**


**30W**  
76mm  
Column  
Entry




**Reducing Lighting Pollution**  
Identify to Urban Spaces




**Elegance and Intelligence**  
A Gentle Glow Brings Safety



**LED Post Top Lantern DIMENSIONS**



**30W LED Post Top Lantern**  
Easy Installation and Maintenance



**DARK SKY FRIENDLY**



**PRODUCT INFORMATION**

LED Type	SMD3030 LEDs
Warranty	5 Year
Part L Compliant	Yes
Dimensions	Ø458 x 659mm
Weight	6.7kg
Windage	0.15m <sup>2</sup>
Equivalent to	70 SON / MHL

**TECHNICAL SPECIFICATIONS**

Power Consumption	30W
Input Voltage	100-280V AC
Power Factor	>0.95
Operating Temperature	-20°C to 65°C
L70 Rated Lifetime	+55,000hrs
Ingress Protection	IP65

**LUMEN PERFORMANCE**

Luminous Efficiency	125lm/W
Beam Angle	150° x 150° (All-round-optic)
CRI (Colour Rendering Index)	>80Ra
Lumen Output	3,750lm

**AVAILABLE OPTIONS**

Colour Temperature	3000K (Dark Sky Friendly- 0% ULOR) 4000K
--------------------	--

## PRODUCT INFORMATION

## TECHNICAL SPECIFICATIONS

## LUMEN PERFORMANCE

### AVAILABLE OPTIONS

3-Hour Emergency Version	No
Built-in Microwave Occupancy Detector	No
1-10V Dimmable	Available on Request
DALI Dimmable	Available on Request

The Top Hat series post-top is a modern designed LED luminaire for column/post mounting at heights of 3 - 7m, suited to general open areas such as pedestrian areas, car parks and low-to-medium traffic urban applications.

IP65 RAL Black die-cast housing finished with a polybonate diffuser, the 360 degree luminaire gives all round uniform illumination with minimal light spillage, capable for reaching 20-30lux from typical 5-6m installations. Furthermore, luminaire compatible with standard external mains photocells for complete dusk-till-dawn control.

Unit C/W Photocell Dusk Til Dawn Sensor

The unit is complete with base mount suitable for 76mm post top column-entry hence universally compatible. Additional benefits include 95lm/W efficacy, +55,000 hour maintenance free performance and minimal disturbance to nocturnal wildlife to the lack of UV/IR spectrum associated with LED photo-metric characteristics.

[DOWNLOAD PRODUCT INSTALLATION MANUAL / GUIDE](#)