

30W LED Post Top Street Lantern Eclipse - 360 Degree Car Park / Street Light Luminaire 30W c/w Photocell Dusk til Dawn Sensor

£240.86

3,750lm

30W
76mm Column Entry



Reducing Lighting Pollution
Identify to Urban Spaces

Elegance and Intelligence
A Gentle Glow Brings Safety

PHOTOCELL READY
Designed for use with photocell sensors to control lighting levels.

SPARK
Designed for safety with a non-fragile lens and a secure mounting.

COLOUR TEMPERATURE
Warm glow (3000K) or cool white (4000K) available.

OPTICAL FINISH
Optimised for light to be directed downwards.

OPTICAL CONTROLS
THE GLASS and the lens are clear.

CLEAR BOWL AESTHETIC
Designed to match the look of a traditional street lamp.


LED Post Top Lantern DIMENSIONS

30W LED Post Top Lantern
Easy Installation and Maintenance

DARK SKY FRIENDLY



3000K*



PRODUCT INFORMATION

LED Type	SMD3030 LEDs
Warranty	5 Year
Part L Compliant	Yes
Dimensions	Ø458mm x 612mm
Weight	6.7kg
Windage	0.27m ²
Equivalent to	70 SON / MHL

TECHNICAL SPECIFICATIONS

Power Consumption	30W
Input Voltage	100-280V AC
Power Factor	>0.95
Operating Temperature	-20°C to 65°C
L70 Rated Lifetime	+55,000hrs
Ingress Protection	IP65

LUMEN PERFORMANCE

Luminous Efficiency	125lm/W
Beam Angle	150° x 150° (All-round-optic)
CRI (Colour Rendering Index)	>80Ra
Lumen Output	3,750lm

AVAILABLE OPTIONS

Colour Temperature	3000K (Dark Sky Friendly- 0% ULOR) 4000K
--------------------	--

PRODUCT INFORMATION

TECHNICAL SPECIFICATIONS

LUMEN PERFORMANCE

AVAILABLE OPTIONS

3-Hour Emergency Version	No
Built-in Microwave Occupancy Detector	No
1-10V Dimmable	Available on Request
DALI Dimmable	Available on Request

The Eclipse series post-top is a modern designed LED luminaire for column/post mounting at heights of 3 - 7m, suited to general open areas such as pedestrian areas, car parks and low-to-medium traffic urban applications.

IP65 RAL Black die-cast housing finished with a polybonate diffuser, the 360 degree luminaire gives all round uniform illumination with minimal light spillage, capable for reaching 20-30lux from typical 5-6m installations. Furthermore, luminaire compatible with standard external mains photocells for complete dusk-till-dawn control.

The unit is complete with base mount suitable for 76mm post top column-entry hence universally compatible. Additional benefits include 95lm/W efficacy, +55,000 hour maintenance free performance and minimal disturbance to nocturnal wildlife to the lack of UV/IR spectrum associated with LED photo-metric characteristics.

[DOWNLOAD PRODUCT INSTALLATION MANUAL / GUIDE](#)