

4ft LED Strip Lights - 1200mm Non-corrosive IP65 Twin/120cm [1.2m] Vapourproof / Weatherproof Batten

\$24.89

5,600lm	<complex-block><complex-block></complex-block></complex-block>
	WURTUR OFTINS WINTER OF IN- OFTINE
PRODUCT INFORMATION	
LED Type	SMD2835 LEDs
Warranty Part L Compliant	5 Year
Part L Compliant Dimensions	Yes 1240mm x 100mm x 84mm
Weight	3.2kg
Equivalent to	1200mm Twin T8
Power Consumption	40W
Input Voltage	220-280V AC
Power Factor	>0.95
Operating Temperature	-20°C to 40°C
L70 Rated Lifetime	+50,000hrs
Ingress Protection	IP65
Emergency Battery Type	LiFePO4 3300Mah Lithium Ion c/w Self Test
LUMEN PERFORMANCE	
Luminous Efficiency	120lm/W
Beam Angle	120°
CRI (Colour Rendering Index)	
Lumen Output	5600lm
AVAILABLE OPTIONS	
Colour Temperature	Natural White 4000K
• -	



PRODUCT INFORMATION

Unit 2, Delta Court, Doncaster, DN9 3GN text_phone 03333 444 943 sales@theledstore.co | https://ledexperts.co.uk/

TECHNICAL SPECIFICATIONS

LUMEN PERFORMANCE

AVAILABLE OPTIONS

3-Hour Emergency Version Yes DMX 512 Compatible No

4ft / 1200mm [1.2m] Twin LED Strip Light - Osram® Driver

LiFePO4 Lithium Ion Emergency Battery - Environmentally friendly, fully recyclable

A revolutionary LED replacement to replace complete non-corrosive fluorescent tube fittings in 1200mm / 4ft twin variety -40W / 5,600lm. With direct illumination technology, prove advantageous over both conventional fluorescents and LED tube counterparts in terms of industry leading efficacy: 120lm/W. Hence an L70 rated lifetime of 30,000+ hour and simple installation, this unit has proved to be the specifiers number one choice being deemed truly 'fit-and-forget'. Wide demand throughout commercial and industrial sectors, namely workshops, high-humidity areas and even outbuildings use being IP65 weather-proof. Toughened polycarbonate diffuser for uniform lumen output with robust PC base. Unit comes complete with stainless steel side clips, detachable hinged tray for ease of install, fixing brackets and M20 x 1.5 IP65 cable gland. Options of 4ft/1200mm, 5ft/1500mm & 6ft/1800mm. M3/NM3 emergency version includes internal built in 3-hour maintained emergency pack.