

LED Street Light with Elexon UMSUG Codes for Unmetered supplies - 30w - 3-6M Column Street Lighting Fixture Flicker Free


\$100.10

4,200lm

30W
Replaces
35W SOX



LED Premium Street Light DIMENSIONS



Performance-Optimized Design & Robust Construction



PHOTOCELL ENABLED



DURABLE, ROBUST AND DEPENDABLE



24/7 CUSTOMER SUPPORT

LED Premium Street Light
Slim and elegant aesthetic
Superior efficacy up to 140 lm/W
Wide range of lumen packages
Self-cleaning Smooth Surface
Tool-Free Access

INSTALLATION INSTRUCTIONS:

1. Remove the mounting bracket from the back of the light fixture.
2. Mount the mounting bracket to the pole using the provided screws.
3. Insert the light fixture into the mounting bracket and secure it with the provided screws.
4. Adjust the light fixture to the desired angle.
5. Tighten the mounting bracket to the pole.
6. The light fixture is now ready for use.

INSTALLATION INSTRUCTIONS:

1. Open the light fixture cover.
2. Connect the wiring to the terminals inside the cover.
3. Close the light fixture cover.
4. Mount the light fixture to the pole using the provided screws.
5. Adjust the light fixture to the desired angle.
6. Tighten the mounting bracket to the pole.

Free Lighting Design Service

Unsure of how many lights you require?
Doubt about light levels, beam angles and lumens?
Don't worry, our expert lighting designers are here to help.
Enquire about our **FREE** no obligation lighting design service.
Turned around in **within just 48 hours!**



PRODUCT INFORMATION

LED Type	SMD3030 LEDs
Warranty	5 Year
Part L Compliant	Yes
Dimensions	617mm x 212mm x 118mm
Weight	3.45kg
Socket Type	Optional 3 pin NEMA Socket
Equivalent to	35 SOX

TECHNICAL SPECIFICATIONS

Power Consumption	30W
Input Voltage	100-280V AC
Power Factor	>0.96
Operating Temperature	-20°C to 50°C
L70 Rated Lifetime	+100,000hrs
Ingress Protection	IP66

PRODUCT INFORMATION**TECHNICAL SPECIFICATIONS****LUMEN PERFORMANCE**

Luminous Efficiency	140lm/W
Beam Angle	150° x 80°
CRI (Colour Rendering Index)	>80Ra
Lumen Output	4,200lm

AVAILABLE OPTIONS

Colour Temperature	Warm White 3000K / Natural white 4000K
3-Hour Emergency Version	No
Built-in Microwave Occupancy Detector	No
1-10V Dimmable	Available on Request
DALI Dimmable	Available on Request

LED Street Light with Elexon UMSUG Codes for Unmetered supplies - 30w - 3-6M Column Street Lighting Fixture Flicker Free

Luminaire designed for column/post mounting at heights of 4 - 16m, with a range of sizes across 30W - 240W (4,200-33,000lm), IP66 design for exterior environments, with a low profile, sleek silver anodised aluminium body for harsh weather environments, Premium Street light is for urban applications such as car-parks, pathways and pedestrian areas. PMMA optic lens ensures a high degree of uniformity across a range of spaces and reduced light spillage, thus further enhancing this 140lm/W luminaire to give optimum lux levels through out. Furthermore the Premium Street light is compatible with standard mains photocells. Additional benefits include 100,000 hours maintenance free performance, with no-tools/quick release access to the internal control gear for installation. Unit available with either 60mm or 76mm entry bracket for both bottom & side-entry hence universally compatible. Angle of illumination can be adjusted around 10° for increased spread.

[DOWNLOAD PRODUCT INSTALLATION MANUAL / GUIDE](#)