



## Solar LED Street Light 18W - All-in-one Solar PV Street Exterior Light c/w Built In Integral Solar Panel & Integrated Lithium LiFePO4 Battery

**£298.00 £249.60**

**12/18W**



**SOLAR ALL IN ONE STREET LIGHT**



**ALL-IN-ONE SOLAR STREET LANTERN**  
100% Energy Savings



**SUITABLE FOR MULTIPLE APPLICATIONS**



**ALL-IN-ONE SOLAR STREET LANTERN**  
Power-Of-Solar-Panel & LiFePO4 Battery




Automated by Dark-to-Dawn Photocell Sensor

Please set Time Control to Maximum Longer Operating Hours

Period	Brightness
3 Hours	100%
3 Hours	80%
6 Hours	20%

**LED Solar Street Lantern DIMENSIONS**



### PRODUCT INFORMATION

LED Type	SMD3030 LEDs
Warranty	5 Year
Part L Compliant	Yes
Dimensions	550mm x 255mm x 87mm 60mm Side Entry
Weight	3.16kg
Windage	0.13m <sup>2</sup>

### TECHNICAL SPECIFICATIONS

Power Consumption	18W
Power Factor	>0.96
Operating Temperature	-20°C to 50°C
L70 Rated Lifetime	+70,000hrs
Ingress Protection	IP66

### LUMEN PERFORMANCE

Luminous Efficiency	180lm/W
Beam Angle	150° x 80°
CRI (Colour Rendering Index)	>80Ra
Lumen Output	3,240lm

### AVAILABLE OPTIONS

Colour Temperature	Natural White 4000-4500K
3-Hour Emergency Version	No
Built-in Microwave Occupancy Detector	Available on Request
1-10V Dimmable	Available on Request
DALI Dimmable	Available on Request

**Solar LED Street Light 18W - All-in-one Solar PV Street Exterior Light c/w Built In Integral Solar Panel & Integrated Battery**

With an integrated Mono-Si solar panel and LiFePO<sub>4</sub> battery, the all-in-one solar LED street lantern makes it easier than ever to meet your sustainability targets. All in a compact housing, you can bring it to both urban and rural areas without access to the electric grid for years to come. The luminaire comes in a range of lumen packages up to 3,600 lumens and is designed for column/post mounting at heights of 3-5m.

With a high tightness level and a very high degree of impact resistance, this luminaire is built to withstand harsh environmental conditions and vandalism to perform over time. High-pressure die cast aluminium housing finished with integrated Mono-Si solar panel which has 25 years anticipated life span, all-in-one solar street lantern gives long lasting and optimised illumination with no uplight pollution. The luminaire is 50mm/60mm side entry as standard, but has the option of an adjustable tilt bracket which mounts direct onto a 76mm column.

All-in-one solar street lantern is made for quick and simple installation without worrying about complicated and frustrating electrical wiring. The luminaire reaches a working time of up to

20-24 hours with as little as 6 hours daily charge. Additional benefits include fully automated from dusk till dawn and pre-set time dimming to maintain optimum performance.

Solar Panel: Mono-si (25 years of anticipated lifespan)

Battery: LiFePO<sub>4</sub> (8 years of anticipated lifespan)

Operating Temperature: 0°C to 40°C

Operating Hours: 20-24 hours (6 hours daily charge)

60MM SIDE ENTRY (ADD ON ADJUSTABLE BRACKET FOR 76MM SHAFT OR SINGLE PROJECTION ARM FOR 76MM SHAFT)

† Calculations are done with the 3 hours of Peak Sun Hour Operation time calculations are done in pre-set time control mode

Operation time calculations are done in pre-set time control mode

Autonomy and Operation time calculations are only indicative and will depend on several variable factors