





**CLEARANCE ** Vandal Proof LED Bulkhead IP65 / IK10 - Outdoor Die-Cast

Aluminium

\$49.90 \$30.52





PRODUCT INFORMATION

SMD2835 LED Type 5 Year Warranty Part L Compliant Yes

Dimensions 320mm x 320mm x 99mm

TECHNICAL SPECIFICATIONS

Power Consumption 18W

100 - 280V AC Input Voltage

Power Factor >0.95

-20°C to 50°C **Operating Temperature** +40,000hrs L70 Rated Lifetime **Ingress Protection** IP65

LUMEN PERFORMANCE

Luminous Efficiency 106lm/W Beam Angle 120° CRI (Colour Rendering Index) >80Ra 1900lm Lumen Output

AVAILABLE OPTIONS

CW 6500-7000K Colour Temperature Available Variant 3-Hour Emergency Version Built-in Microwave Occupancy Detector Available Variant 1-10V Dimmable Available Variant



PRODUCT INFORMATION

Unit 2,
Delta Court,
Doncaster,
DN9 3GN
text_phone 03333 444 943
sales@theledstore.co | https://ledexperts.co.uk/

TECHNICAL	CDECIE	CATIONIC
IF(HNICAL	SPEC IFI	CALICINS

LUMEN PERFORMANCE

AVAILABLE OPTIONS

DALI Dimmable

Available Variant

**CLEARANCE ** A complete LED replacement suitable for stairwells, walk ways, undercrofts as well as outdoor use being IP65 rated. With an anti-glare frosted toughened diffuser for uniform, subtle light output up to 1900lm, this unit is designed to be a direct replacement for 28W 2D-flourescents, whilst boasting efficacy of up to 106lm/W. Hence energy savings over flourescent counterparts in the region of 35-40% with an equivalent reduction in utilities. Other benefits include minimised maintenance rated at 30,000 hours, high light output even in cold temperatures and minimised distrubance to wildlife due to non ultra violet light. Further options include intergal 3-hour emergency pack with self-test function as well as built in microwave sensore for intelligent occupancy control: adjustable dimming (up to 25%), sensitivy range (180° / 0.5m - 8m) and duration (10secs - 5mins).

DOWNLOAD PRODUCT INSTALLATION MANUAL / GUIDE